

➔ Specifications

Parameter	Specification
Center Wavelength (λ_c)	1064 nm
Bandwidth	± 20 nm
Insertion Loss	0.8 dB (0.6 dB typ.)
Extinction Ratio	20 dB (22 dB typ.)
Directivity	50 dB
Return Loss	45 dB
Fiber Type of Port 1 & 2	PM 980 Panda Fiber
Fiber Type of Port 3	HI 1060 or PM 980 Panda Fiber
Maximum Power	300 mW
Fiber Tensile Load	5 N
Operating Temperature	0° C ~ + 70° C
Storage Temperature	- 40° C ~ + 85° C
Package Dimensions	5.5 mm (ϕ) x 35 mm (L)

Note1: All values specified are without connectors.

Note2: Higher performance specifications available upon request.

➔ Ordering Information

P	B	S	-	1	0	6	4	-		-	A	-		-		-				
				Center Wavelength							Fiber Type for Port 3			Fiber Length			Pigtail Style			Connector
				1064: 1064 nm							S: HI 1060 fiber P: PM fiber			A: 1 meter			(=Package style) B: bare fiber L: 900 μ m loose tube			0: None 7: LC/UPC 1: FC/PC 8: LC/SPC 2: FC/APC 9: Special 3: SC/PC A: FC/UPC 4: SC/APC B: SC/UPC 5: FC/SPC C: ST 6: SC/SPC