

➔ Specifications

Parameter	Premium	A Grade
Operating Wavelength Range	1311 & 1550 ± 40 nm	
Insertion Loss (Max)	5.6 dB	5.9 dB
Uniformity (Typical)	1.2 dB	1.6 dB
Return Loss	50 dB	
PDL	0.10 dB	0.15 dB
TDL	0.2 dB (-10°C ~ +75°C)	0.4 dB (-40°C ~ +85°C)
Operating & Storage Temperature	- 40° C ~ + 85° C	
Package Dimensions	Light Duty (B)	3.0mm () x 55.0mm (L)
	Medium Duty (L)	3.0mm () x 70.0mm (L)

Note1: All values specified are without connectors.

Note3: Fiber Type – Corning SMF-28e.

➔ Ordering Information

<u>D</u>	<u>W</u>	<u>W</u>	<u>C</u>	-	<u>1</u>	<u>3</u>	-	<u>Grade</u>	-	<u>EVEN</u>	-	<u>Wavelength</u>	-	<u>Fiber Length</u>	-	<u>Pigtail Style</u>	-	<u>Connector</u>
								P: Premium A: A Grade		EVEN: 33/33/34		E: 1310 nm F: 1480 nm G: 1510 nm H: 1550 nm L: 1625 nm		1: 1 meter 2: 2 meter S: Special		(=Package style) B: bare fiber L: 900 μm loose tube		0: None 7: LC/UPC 1: FC/PC 8: LC/SPC 2: FC/APC 9: Special 3: SC/PC A: FC/UPC 4: SC/APC B: SC/UPC 5: FC/SPC C: ST 6: SC/SPC