

➔ Specifications

Parameter	Mux	Demux
Operating Wavelength Range	1460-1620 nm	
Channel Spacing	20 nm	
Channel Number	8	
Center Wavelength (c)	1471, 1491, 1511, 1531, 1551, 1571, 1591, & 1611 nm	
Pass Band	c ± 6.5 nm	
Insertion Loss	3.4 dB	
Pass Band Ripple	0.5 dB	
Adjacent Channel Isolation	NA	45 dB
Non-Adjacent Channel Isolation	NA	50 dB
Return Loss	45 dB	
Directivity	50 dB	
PDL	0.2 dB	
PMD	0.2 ps	
Maximum Power Handling	300 mW	
Operating Temperature	- 5° C ~ + 70° C	
Storage Temperature	- 40° C ~ + 85° C	
Package Dimensions	70 mm x 40 mm x 9.5 mm	

Note1: All values specified are without connectors.

➔ Ordering Information

C	C	W	D	M	H	8	-	-	-	-	-
							-	-	-	-	-
							Module Type	Fiber Length	Pigtail Style	Connector	
							M: Mux	A: 1 meter	(=Package style)	0: None	7: LC/UPC
							D: Demux	B: 1.5 meter	B: bare fiber	1: FC/PC	8: LC/SPC
									L: 900 μm loose tube	2: FC/APC	9: Special
										3: SC/PC	A: FC/UPC
										4: SC/APC	B: SC/UPC
										5: FC/SPC	C: ST
										6: SC/SPC	