

➔ Specifications





Parameter	Premium	A Grade
Operating Wavelength Range	980 nm / 1030 nm ± 5 nm	
Insertion Loss	0.5 dB	0.7 dB
Isolation	12 dB	10 dB
TDL	0.2 dB	
Return Loss	55 dB	
PDL	0.1 dB	
Operating & Storage Temperature	- 40° C ~ + 85° C	
Package Dimensions	Light Duty (B)	3.0mm () x 60.0mm (L)
	Medium Duty (L)	3.0mm () x 65.0mm (L)
	Heavy Duty (K, R)	100.0mm x 12.0mm x 8.0mm

Note1: All values specified are without connectors.

Note2: Higher performance specifications available upon request.

Note3: Fiber Type – OFS 980 fiber unless otherwise specified.

➔ Ordering Information

W	D	M	6	-		-		-		-		-	
					Port Number		Grade		Fiber Length		Pigtail Style		Connector
					12: 1 x 2 22: 2 x 2		P: Premium A: A Grade		1: 1 meter 2: 2 meter S: Special		(=Package style) B: bare fiber L: 900 μm loose tube K: 2mm cable R: 3mm cable		0: None 7: LC/UPC 1: FC/PC 8: LC/SPC 2: FC/APC 9: Special 3: SC/PC A: FC/UPC 4: SC/APC B: SC/UPC 5: FC/SPC C: ST 6: SC/SPC